

RT-1M05

Mono-Directional Filament Tape

**Product Description**

RT-1M05 is a light strength fiberglass reinforced biaxially-oriented polypropylene (Bopp) or polyester (pet) film tape with a aggressive solventless pressure sensitive hot melt adhesive. Exhibits high impact strength excellent adhesion to kraft cartons and bundling applications.

Main Application

- * Unitizing
 - * Strapping
 - * Packaging
 - * Transport securing
 - * Bundling and palletizing
-

Construction

*Backing:	Pet/Bopp film	*Adhesive:	Pressure sensitive hot melt
*Backing Color:	Clear	*Reinforcement:	Mono-directional glass yarn

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes. Test before massive using is recommended.

Total Thickness:	0.12 ± 0.01mm	ASTM D-3652
Adhesion to Steel (180°):	15 N / inch	ASTM D-3330
Tensile strength:	450 N/25mm	ASTM D-3759
Elongation at Break:	6~12%	ASTM D-3759

Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 4~26 °C (40~80 °F) and 40~50% relative humidity are recommended. Rotate your stock.

Rudder(Xiamen) Industrial Co.,Ltd.

#316-5D, Dongfang Commercial Mansion,
No56 Yibin North Road, 361000,
Xiamen Area of China (Fujian) Pilot Free Trade Zone.

E: info@ruddertape.com
Website: www.ruddertape.com

Rudder Tape prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.
