

Rudder Tape

info@ruddertape.com


www.ruddertape.com

RT-1M8C

Mono-directional Filament Tape

Product Description

RT-1M8C is a medium strength fiberglass reinforced biaxially-oriented polyester (Pet) film tape with solvent acrylic based adhesive with clean removal charteristic. Exhibits steady adhesion to wrapping and bundling applications, etc.



Main Application

- * Steeling coil bundling,
- * Electrical equipment uses
- * Home appliance uses
- * Transport securing, etc

Construction

*Backing: Polyester film *Adhesive: Solvent Acrylic based

*Backing Color: Clear *Reinforcement: Mono-directional continuous glass yarn

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes. Test before massive use is recommended.

Typical Physical Properties

Total Thickness: 0.12 ± 0.01mm ASTM D-3652 Adhesion to Steel (90°): ≥ 10 ± 2 N / in ASTM D-3330 Tensile strength: ≥ 520 N/ 25mm ASTM D-3759 Elongation at Break: $3\sim5\%$ ASTM D-3759

Service Temperature -20°C ~120°C

Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 4~26 $^{\circ}$ C (40~80 $^{\circ}$ F) and 40~50% relative humidity are recommended. Rotate your stock.

Rudder(Xiamen) Industrial Co.,Ltd.

#316-5D, Dongfang Commercial Mansion, No56 Yibin North Road, 361000, Xiamen Area of China (Fujian) Pilot Free Trade Zone.

E: info@ruddertape.com Website: www.ruddertape.com Rudder Tapes products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.