

## RT-2WR06

REINFORCED WATER ACTIVATED TAPE

### Product Description

Reinforced by 3-way fiberglass and manufactured with water activated adhesive for kraft carton sealing. The fiberglass yarn provide consistent performance in carton sealing applications where durability, extra strength and reliability are required.



### Application

Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads. Using on the light weight carton up to 31 lbs is recommended.

### Physical Properties

Thickness	0.15±0.01mm	(5.9mil)
MD Tensile	≥ 61 lbs/in	(270 N/25mm)
CD Tensile	≥ 26 lbs/in	(113 N/25mm)

### Construction

Top Ply:	23 lb	Virgin Natural Kraft Paper and virgin fibers
Bottom Ply:	23 lb	Virgin Natural Kraft Paper and virgin fibers
MD Reinforcement:	(1-1-1-1-1)	110 Fiberglass per 72mm
CD Reinforcement:	(1-1-1-1)	150 Fiberglass, 1" spacing, at 45° angle
Laminating Adhesive:	Hot Melt Adhesive	
Water-Activated Adhesive:	Starch Based Adhesive	

### Storage Conditions

A clean place is recommended.

### Rudder(Xiamen) Industrial Co.,Ltd.

#316-5D, Dongfang Commercial Mansion,  
No56 Yibin North Road, 361000,  
Xiamen Area of China (Fujian) Pilot Free Trade Zone.

E: info@ruddertape.com  
Website: www.ruddertape.com

This product is believed to be reliable, whilst the statements and information about it are only for general guidance and are not warrants or guarantees for accuracy and completeness. It should be tested by the user before determining suitability for the purpose. There is no warranty of fitness for a particular purpose. These standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No any oral warranties can be made by us. We reserve all rights to make changes without notice or obligation in our products and publications.