

RT-112

Mono-directional Filament Tape

Product Description

RT-112 is heavy grade fiberglass reinforced biaxially-oriented polyester film tape with a aggressive solventless pressure sensitive synthetic rubber and resin adhesive. Exhibits steady strength excellent adhesion to strapping, palletizing, bundling applications, etc.



Main Application

- * Unitizing
- * Strapping
- * Packaging
- * Transport securing,
- * Bundling and palletizing, etc

Construction

*Backing:	25 mic Polyester film	*Adhesive:	Pressure sensitive synthetic rubber and resin
*Backing Color:	Clear	*Reinforcement:	Mono-directional continuous glass yarn

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Typical Physical Properties

Total Thickness:	0.20 mm	7.9 mil		ASTM D-3652
Adhesion to Steel:	22 N/25mm	79 oz/ in		ASTM D-3330
Tensile strength:	2,000 N/25mm	449 lbs/in	81.63 kg/cm	ASTM D-3759
Elongation at Break:	3~5%			

Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 4~26 °C (40~80 °F) and 40~50% relative humidity are recommended. Rotate your stock.

Rudder(xiamen) Industrial Co.,Ltd.

#316, No 56 Yibin North Road, 361000,
Xiamen Area of China (Fujian) Pilot Free Trade Zone.

E: info@ruddertape.com
Website: www.ruddertape.com

Rudder Tape prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.