

RT-1C11

Bi-directional Filament Tape

Product Description

It is coated by 25mic polyester film woven with cross fiberglass reinforcements with a pressure-sensitive synthetic rubber and resin adhesive. Balanced machine direction and cross direction tensile strength, high adhesion and medium impact strength. Bi-directional filaments provide resistance to delamination for improved one piece removability and increased "boardiness" for automatic application.



Main Application

- * Unitizing
- * Bundling,
- * Palletizing,
- * Strapping
- * Sealing, etc

Construction

*Backing:	Polyester film	*Adhesive:	Pressure sensitive synthetic rubber and resin
*Color:	Clear	*Reinforcement:	Bi-directional continuous glass yarn

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Typical Physical Properties

Total Thickness:	0.15 mm	5.9 mil		ASTM D-3652
Adhesion to Steel:	30 N/25mm	108 oz/ in		ASTM D-3330
Tensile strength:	600 N/25mm	135 lbs/in	24.49 kg/cm	ASTM D-3759
Elongation at Break:	3~5%			ASTM D-3759
Service Tem recommended:	0°C to 85°C			

Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 4~26 °C (40~80 °F) and 40~50% relative humidity are recommended. Rotate your stock.

Rudder(xiamen) Industrial Co.,Ltd.

#316, No 56 Yibin North Road, 361000,
Xiamen Area of China (Fujian) Pilot Free Trade Zone.

E: info@ruddertape.com
Website: www.ruddertape.com

Rudder Tape prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.