

RT-1D04

Double-Sided Filament Tape

Product Description

It is a double-sided cross weave filament tape coated by 70 um release paper-glassine paper. The bi directional fiberglass yarn provides high strength. Synthetic rubber and resin adhesive provides good adhesion to a variety of surfaces.



Main Application

- * Insulation layer sticks uses
- * Stick plastic articles uses
- * Non-weaving fabrics and PU
- * etc

Construction

*Liner:	Tan release paper	*Adhesive:	Synthetic rubber and resin
*Liner color:	Tan	*Reinforcement:	Bi-directional glass yarn

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Total Thickness:	235 um	ASTM D-3652
Adhesion to Steel:	≥ 60 oz/in ≥ 6.8 N/cm	ASTM D-3330
Tensile strength:	≥ 98 lbs/in ≥ 175.2 N/cm	ASTM D-3759
Elongation at Break:	3~5%	ASTM D-3759
Service Tem recommended:	-7 ~85°C (20 ~185°F)	

Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 4~26 °C (40~80 °F) and 40~50% relative humidity are recommended. Rotate your stock.

Rudder(Xiamen) Industrial Co.,Ltd.

#316, No 56 Yibin North Road, 361000,
Xiamen Area of China (Fujian) Pilot Free Trade Zone.

E: info@ruddertape.com
Website: www.ruddertape.com

Rudder Tape prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R. T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.