

Rudder(xiamen) Industrial Co.,Ltd.

info@ruddertape.com

www.ruddertape.com


RT-1M12C

Electric Filament Tape

Product Description

- Adhesive tape with reinforced backing
- Ideal electrical insulating product
- Polyester film with glass filament reinforcement
- Excellent heat resistance

- Superior tensile strength and adhesion



Alternative to WET 248 etc

Main Application

- -Oil filled distribution transformers
- Engineered for use as construction tape for various holding and banding function as for fixing the insulation paper or pressboard at the transformer windings production
- Fixing the insulation paper at the beginning of the LV foil and for bandaging of the outer wrap insulation of A10windings
- Wire insulation reinforcement

St	trι	ıct

*Backing: Polyester film *Adhesive: Thermosetting Acrylic Adhesive

*Color: Transparent *Reinforcemen Mono-directional continuous glass yarn

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Typical Physical Properties

Total Thickness:	0.190	mm	7.5	mil		ASTM D-3652
Adhesion to Steel:	15	N/25mm	54	oz/ in		ASTM D-3330
Tensile strength:	1,600	N/25mm	360	lbs/in	65.31 kg/cm	ASTM D-3759
Elongation at Break:	3~5%					ASTM D-3759
Breakdown Voltage	≥6 KV					
Temperature Class	155°C	(F)				

Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 4~26 °C (40~80 °F) and 40~50% relative humidity are recommended. Rotate your stock.

Rudder(xiamen) Industrial Co.,Ltd.

#316, No 56 Yibin North Road, 361000, Xiamen Area of China (Fujian) Pilot Free Trade Zone.

E: info@ruddertape.com Website: www.ruddertape.com Rudder Tape prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.