

RT-550S

Golf Grip Tape

Product Description

White release paper as liner, coated with solvent acrylic adhesive, Non-woven tissue as carrier.
Strong adhesion & holding power, superior adhesive strength on various kinds of backing materials, especially suitable for bonding materials onto rough surfaces.

1. Good anti-aging, high adhesion,
2. Suitable for sealing plastic bags, sticking wallpaper, splicing paper,
3. Suitable for nameplate sticking, punching, leather, embroidery, EVA/foam, Sport facility etc.

Construction

Liner:	105±5 gsm White release paper	Adhesive	Solvent Acrylic Glue
Carrier	Non-woven tissue	Color	Translucent

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Typical Physical Properties

Thickness (mic):	90	
Initial Tack #14 Steel Ball (mm)	≤100	GB/T 4852-2002
Peeling Strength (N/25mm)	≥12	GB/T 2792-1998
Holding Power 25 Celsius (minute)	≥300	GB/T 4851-1998

Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 4~26 °C (40~80 °F) and 40~50% relative humidity are recommended. Rotate your stock.

Navi Rudder Indo Co., Limited.
Rudder(xiamen) Industrial Co., Ltd.

#316, No 56 Yibin North Road, 361000,
Xiamen Area of China (Fujian) Pilot Free Trade Zone.
E: sales@ruddertape.com
Website: www.ruddertape.com

Rudder Tape prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.