

**RT-1101**

High Strength Mono-directional Filament Tape



**Product Description**

It is a heavy grade fiberglass reinforced biaxially-oriented polyester film tape with an aggressive solventless pressure sensitive synthetic rubber and resin adhesive. Exhibits steady strength excellent adhesion to kraft cartons and bundling applications, etc.

**Main Application**

- \* Unitizing
- \* Strapping
- \* Packaging
- \* Transport securing,
- \* Bundling and palletizing, etc

**Construction**

*Backing:	Polyester film	*Adhesive:	Pressure sensitive synthetic rubber and resin
*Color:	Clear	*Reinforcement:	Mono-directional continuous glassfiber yarn

**Typical Physical Properties**

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Typical Physical Properties

Total Thickness:	0.28 mm	11.0 mil	ASTM D-3652
Adhesion to Steel:	25 N/25mm	90 oz/ in	ASTM D-3330
Tensile strength:	3,000 N/25mm	680 lbs/in	ASTM D-3759
Elongation at Break:	3~5%		

Tolerance: Tension ±50N/25mm, Adhesion: ±5N/25mm, Thickness: ±0.01mm

**Storage Conditions**

Store behind present stock. Store in a clean, dry place. Temperature of 4~26 °C (40~80 °F) and 40~50% relative humidity are recommended. Rotate your stock.

Rudder(Xiamen) Industrial Co.,Ltd.

E: sales@ruddertape.com  
Website: www.ruddertape.com

Rudder Tape prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.