

Rudder (Xiamen) Industrial Co.,Ltd.

sales@ruddertape.com


www.ruddertape.com

RT-DS501

Double-sided Tissue Tape

Product Description

Non-woven tissue as carrier and coated with Solvent Acrylic Glue based, it owns features includes: strong cohesion, good aging resistance, superior temperature resistance, PP, PE, PU, foam, chemical fiber, kapok cloth and other materials have good adhesion, the main use of insulation materials, insulation materials, shock, sound insulation, decorative board dust net, dust ceiling, home appliances and other materials paste. Especially suitable for rough and greasy surface and other materials bonding.



Main Application

Good anti-aging, high adhesion

The main use of insulation materials, insulation materials, shock, sound insulation, decorative board dust net, dust ceiling, home appliances and other materials paste. Especially suitable for rough and greasy surface and other materials bonding, EVA/foam, etc.

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Typical Physical Properties				Storage Cond
Test Item	Unit	Typical test value		store in a dry to 30 °C, store organic solver nor rolling and Based on the adhesive tape 1) the use of a suggested cor RH;Please do below 15 °C; 2) before past adhesive is cl 3) in order to play to its stic at one end first 1.5kg/cm2 or under the present of the solver in the present to the store of the store of the solver in the present to solver in the solver in
Carrier	-	Non-woven Tissue	-	
Thickness: Without liner	um	140±5	GB/T7125-2014	
Adhesive	-	Acrylic Glue	-	
Color	-	Translucent	-	
Peel Adhesion at 180°	N/25mm	≥15	GB/T2792-2014	
Temperature resistance	°C	80	GB/T4851-2014	
Liner		White Release Paper		

Storage Conditions

y cleaning, the temperature is 5 $^\circ \! \mathbb C$ age life for a year, to avoid ents, sharp objects during storage, nd throws.

e properties of pressure-sensitive e, we sincerely recommend:

- adhesive tape conditions ontrol for 20 ~ 30 ~ 35 ℃, 60% on't do paste operation when
- sting, make sure the surface of the clean and dry;
- make the adhesive belt give full ckiness, it is suggested to paste it rst, and apply pressure of
- more to the other end slowly emise of the adhesive material.

Rudder(Xiamen) Industrial Co.,Ltd.

E: sales@ruddertape.com Website: www.ruddertape.com Rudder Tape products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.