


RT-DS602

Double-sided Tissue Tape

Product Description

Non-woven tissue as carrier and coated with pressure sensitive synthetic rubber resin adhesive based, it owns features includes: strong cohesion, good aging resistance, superior temperature resistance, PP, PE, PU, foam, chemical fiber, kapok cloth and other materials have good adhesion, the main use of insulation materials, insulation materials, shock, sound insulation, decorative board dust net, dust ceiling, home appliances and other materials paste.Especially suitable for rough and greasy surface and other materials bonding.



Main Application

Good anti-aging, high adhesion

The main use of insulation materials, insulation materials, shock, sound insulation, decorative board dust net, dust ceiling, home appliances and other materials paste.Especially suitable for rough and greasy surface and other materials bonding, EVA/foam, etc.

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Typical Physical Properties

Test Item	Unit	Typical test value	Test method
Carrier	-	Non-woven Tissue	-
Thickness: Without liner	um	135±5	GB/T7125-2014
Adhesive	-	Synthetic Rubber Resin Adhesive	-
Color	-	Translucent	-
Peel Adhesion at 180°	N/25mm	≥32	GB/T2792-2014
Initial Tack	#	15	-

Storage Conditions

Store in a dry cleaning, the temperature is 5 °C to 30 °C, storage life for a year, to avoid organic solvents, sharp objects during storage, nor rolling and throws.

Based on the properties of pressure-sensitive adhesive tape, we sincerely recommend:

- 1) the use of adhesive tape conditions suggested control for 20 ~ 30 ~ 35 °C, 60% RH;Please don't do paste operation when below 15 °C;
- 2) before pasting, make sure the surface of the adhesive is clean and dry;
- 3) in order to make the adhesive belt give full play to its stickiness, it is suggested to paste it at one end first, and apply pressure of 1.5kg/cm2 or more to the other end slowly under the premise of the adhesive material.

Liner White Release
Paper

Rudder(Xiamen) Industrial Co.,Ltd.

E: sales@ruddertape.com

Website: www.ruddertape.com

Rudder Tape products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.