

Rudder (Xiamen) Industrial Co.,Ltd.

sales@ruddertape.com

www.ruddertape.com

RT-M7002

Medium Temperature Masking Tape

Product Description

RT-M7002 is a masking tape backing with crepe paper and coated with pressure sensitive water based acrylic adhesive. Good holding and sealing properties make it fits for painting, spray painting and other applications on packaging, sealing, bundling, stationery, metal, shoe materials, sports equipments, electronic parts and components, also ideal for auto repair and maintenance and so on.

Ideal for applications:

House decoration, painting

Light object binding and fixing

Physical Properties					Test Method
Backing material	Crepe Paper				
Color	Blue				
Adhesive	Water Based Acrylic Adhesive			е	
Total Thickness	0.135	±0.1mm	5.3	mil	ASTM D-3652
Adhesion to Steel (180 °)	2.5	N/25mm	9.00	oz/ in	ASTM D 3330
Tensile Strength	28	N/25mm	6.29	lbs/in	ASTM D 3759
V Resistance 14 days		14 days			
Service Temp Recommended	up to 1	00 °C	up to 212°F		

Note:

- 1. The data above are typical values only, and should not be used for specifications purpose.
- 2. Tolerance: Thickness: ±10µm; Width: ±1mm; Length: Cut Roll: ±0.3m, Jumbo Roll ±0.5%.
- 3. Jumbo Size: 1,270 mm x 1,800 m

Storage and Shelf Life

Shelf life 12 months from date of production. Tapeshould be stored in a cool (temperature between $15^{\circ}\text{C} \sim 35^{\circ}\text{C}$), dry (humidity between $40\% \sim 75\%$) environment.

Well ventilated area away from sunlight, air conditionerand other heat sources.

Surface Preparation:

It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants

Rudder(Xiamen) Industrial Co.,Ltd.

E: sales@ruddertape.com Website: www.ruddertape.com Rudder Tape is believed to be reliable, whilst the statements and information about it are only for general guidance and are not warrants or guarantees for accuracy and completeness. It should be tested by the user before determining suitability for the purpose. There is no warranty of fitness for a particular purpose. These standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No any oral warranties can be made by us. We reserve all rights to make changes without notice or obligation in our products and publications.