

RT-D1027

Duct Tape

Product Description

Backing with PE cloth as carrier, coated with modified hot melt based adhesive.
Good at oli resistant, aging resistant, anti-corrosion, water-proofing, etc.

Main Applications

Duct wrapping
Packaging
Decoration
Bundling
Floor marking etc

Construction

*Backing: PE
*Adhesive: Modified Hot Melt Based
*Color: Red, Black, Grey etc

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Typical Physical Properties

Total Thickness:	0.27	mm	10.6	mil	ASTM D-3652
Adhesion to Steel (180°):	19	N/25mm	68	oz/ in	ASTM D-3330
Tensile strength:	75	N/25mm	17	lbs/in	ASTM D-3759
Elongation at Break:	10%				

Note: thickness±0.01mm, adhesion ±2N/25mm, tension:±5N/25mm

Jumbo size: 1,060mm x 1,000m

Shelf-life: 12 months after the date of production

Storage Conditions

Store behind present stock. Store in a clean, dry place. Temperature of 4~26 °C (40~80 °F) and 40~50% relative humidity are recommended. Rotate your stock.

[Rudder\(Xiamen\) Industrial Co.,Ltd.](#)

E: sales@ruddertape.com
Website: www.ruddertape.com

Rudder Tape prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommends are provided to the best of our knowledge on the basis of our practical experience. Nevertheless R.T can make no warranties, express or implied, including, but no limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to advise you.