

## RT-H103

Hot Melt Adhesive for Adhesive Tape

### Product Description

RT-H103 is widely used for sorts of hot melt based adhesive tape.  
Excellent fluidity.  
High initial tack  
Good holding power

### Typical Physical Properties

Product	Hot Melt Adhesive	
175° Consistence (CPS)	5000-6000	
Softening Point (°C)	105 ± 5 °C	(around 221 ° F)

Note: The following technical information and data should be considered representative or typical only, and not for specification purposes.

### Applications recommended :

Fiberglass Tape  
Tissue Tape  
Cloth Duct Tape  
Aluminum Foil Tape  
PE Courier Bag  
Bubble Bag, etc



Fiberglass tape

Tissue tape

Cloth

Rudder(Xiamen) Industrial Co.,Ltd.

Rudder Tape prove their impressive quality day in, day out in dem are regularly subjected to strict controls. All information and recor the best of our knowledge on the basis of our practical experience make no warranties, express or implied, including, but no limited t of merchantability or fitness for a particular purpose. Therefore, th for determining whether the R.T products is fit for a particular purp the user's method of application. If you are in any doubt, our staff you.

E: sales@ruddertape.com  
Website: www.ruddertape.com

---

ould not be used



### h duct tape

anding conditions and  
mends are provided to  
. Nevertheless R.T can  
o any implied warranty  
ie user is responsible  
ose and suitable for  
will be glad to advise