

RT-H201

Modified Pressure Sensitive Hot Melt Adhesive

Product Description

Based on particular formula, ideal for Adhesive Tape, Paper, Glass, Plastic products, ABS applications, etc.

Main feature

Good Weather Resistance

High Bonding Strength

Smokeless & Odorless etc

Typical Physical Properties

| | | | |
|----------------------|------------------------|------------------------|---------------|
| Color | Yellowish Transparent | Viscosity (Brookfield) | |
| Basic material | PSA/ Synthetic Resin | Viscosity (CPS) | 6700±1000 |
| Softening Point (°C) | 99 ± 5 (Ring and Ball) | Temperature | 170°C |
| | | Application Temp | 150°C ~180 °C |

Application Method Glue Machines

FDA Status Products compositions meet requirement of in-direct food additives regulation 21 CFR 175. 105 Adhesive

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Storage Conditions

Store behind present stock. Store in a clean, dry place. Glue applicator is hot, avoid touching any part of the applicator other than its glue tank handle when adding new glues

[Rudder\(Xiamen\) Industrial Co.,Ltd.](#)

E: sales@ruddertape.com
Website: www.ruddertape.com

Rudder Tape prove their impressive quality day in, day out in demanding conditions. All information and recommends are the best of our knowledge on the basis of our practical experience. Nevertheless, we make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the R.T products is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our staff will be glad to help you.

)-

re used

other

ditions and
provided to
ss R.T can
d warranty
ossible
table for
to advise
